

# MODEL 4351E CONVENTIONAL HIGH TEMPERATURE THERMAL DETECTOR

series 300

## FEATURES

- Low profile design
- Low current draw
- Backward compatible with Series 100 detector range of bases
- Wide operating voltage 8 to 30V
- Bi-colour LED detector status indicator
- Programmable sensitivity
- Addressable feature
- Advanced maintenance features via remote hand-held test unit
- Range of detector bases available
- Tested and approved to EN54 part 5 (2000) Class BS
- Extended warranty



## DESCRIPTION

The 4351E thermal detector forms part of the Series 300 range of conventional detectors. This range of detectors has been produced using the latest in manufacturing and design techniques, pushing out the boundaries of existing conventional detector technology. With its multitude of innovative features, the Series 300 is a detector which 'acts conventionally, thinks intelligently'.

The 4351E thermal detector incorporates an Application Specific Integrated Circuit (ASIC). Combined with the latest in thermal element technology the detector provides efficient and accurate detection of fires, especially in environments such as boiler houses or kitchens where smoke detectors are inappropriate due to the high level of airborne contamination.

The 4351E and other detectors in the Series 300 range are backward compatible with the Series 100 detector bases, thus providing the capability to upgrade, extend and maintain existing Series 100 installations.

The 4351E detector incorporates a bi-colour LED indicator. The integral LED changes colour according to the detector's status - Green = Normal, Red = Alarm. This benefits the user by providing clear, instant visual indication of the detector's condition. The Green LED can be programmed for blink/no blink operation.

The remote hand-held programming unit can also be used in conjunction with the Series 300 range of detectors to gain access to other advanced features. The features available include: read/write last maintenance date, read value of thermal element and perform an alarm test.

Each unit can be given a unique address that will be displayed on the S300ZDU whenever the detector is in alarm.

All the features via the hand-held programming unit are achieved effectively and effortlessly without the need to remove the detector or having to gain direct physical access (other than by the use of 'No Climb Products' or similar servicing tool), saving valuable commissioning/maintenance time.

They provide the end user with the confidence to know that his system is being regularly serviced and that it is operating at its optimum level, with minimum disruption to his own business activities.

**EUROPEAN HEADQUARTERS**  
**SYSTEM SENSOR EUROPE**  
**3 HORSHAM GATES**  
**HORSHAM**  
**WEST SUSSEX**  
**RH13 5PJ**  
**UNITED KINGDOM**  
**TEL: +44 (0)1403 276500**  
**FAX: +44 (0)1403 276501**  
**EMAIL: sales@sseuk.com**

**EUROPEAN MANUFACTURING CENTRE**  
**PITWAY TECNOLOGICA SPA**  
**VIA CABOTO 19/3**  
**34147 TRIESTE**  
**ITALY**

**TEL: +39 040 9490111**  
**FAX: +39 040 382137**

[www.systemsensoreurope.com](http://www.systemsensoreurope.com)



**SYSTEM  
 SENSOR®**

## MODEL 4351E HIGH TEMPERATURE THERMAL DETECTOR

In addition to the comprehensive programming tool, a simple laser based alarm test unit is also available. The coded signal transmitted by this device can instruct the detector to generate a full alarm condition at a range of up to 5 metres from the detector, and is an ideal tool for initial commissioning and routine system testing.

A variety of detector bases can be used with the 4351E detector, providing application flexibility and compatibility with a wide range of Fire Alarm Control Panels. All bases are fitted with a shorting spring to permit circuit testing prior to fitting the detector and have a tamper resistant feature, which when activated prevents removal of the detector without the use of a tool.

All System Sensor products are covered by our extended 3 year warranty.

### SPECIFICATIONS

#### Electrical

Operating Voltage Range	8 to 30VDC (Nominal 12/24VDC)
Maximum Standby Current (Typical)	140µA
Maximum Permissible Alarm Current (LED On)	50mA at 24VDC (Limited by panel)

#### Environmental

Operating Temperature Range (see note 1)	-30°C to +80°C
Humidity	5 to 95% Relative Humidity (non-condensing)

#### Mechanical

Height	43mm
Diameter	102mm
Weight	75g
Max Wire Gauge for Terminals	1.5mm <sup>2</sup>
Colour	Pantone, warm grey 1C
Material	Bayblend FR110

#### Product Range

Bases (See Note)	B401 Standard Base B401SD Standard base with schottky diode B401R Resistor base with 470 ohm resistor B401RSD Standard base with 470 ohm resistor and Shottky diode B401RM Standard recess base with 470 ohm resistor B401DG Deep base B401DGR Deep base with 470 ohm resistor B401DGSD Deep base with Shottky diode B312NL 12V non-latching relay base B312RL 12V latching relay base B324RL 24V latching relay base
------------------	---

#### Accessories

S300RPTU Remote Programming and Test Unit  
S300RTU Remote Test Unit  
S300SAT Remote Programming Interface Unit  
S300ZDU Zonal Display Unit

#### Other Detectors

2351E, 2351TEM, 5351E

#### Notes:

(1) To avoid unwanted alarm conditions being triggered by class BS detectors maximum ambient operating temperature should not exceed 68°C.

(2) Bases with other resistor values are available to suit the requirements of most Fire Alarm Control Panels.